

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/006268 A3

(51) International Patent Classification⁷: **G21F 9/16**,
9/30, 9/34

(21) International Application Number:
PCT/GB2003/002870

(22) International Filing Date: 3 July 2003 (03.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0215341.9 3 July 2002 (03.07.2002) GB

(71) Applicant (for all designated States except US): **BRITISH NUCLEAR FUELS PLC** [GB/GB]; Risley, Warrington, Cheshire WA3 6AS (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HOLLICK, Adele, Charmaine** [GB/GB]; British Nuclear Fuels Plc, Risley, Warrington, Cheshire WA3 6AS (GB). **HANIGAN, Nicholas, Paul** [GB/GB]; British Nuclear Fuels Plc, Risley, Warrington, Cheshire WA3 6AS (GB).

(74) Agent: **CHALK, Anthony, John**; Harrison Goddard Foote, Belgrave Hall, Belgrave Street, Leeds LS2 8DD (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
18 March 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: STORAGE OF HAZARDOUS MATERIALS

(57) Abstract: The invention provides a method for the encapsulation of a nuclear material, which comprises treating the material with an encapsulant, which comprises a cementitious material, such as Portland Cement, and curing, said cementitious material. The method is particularly suitable for the treatment of nuclear fuel materials such as uranium metal, complete Magnox fuel elements, or fuel element debris, for which encapsulation treatments have never previously been known. Such materials may be treated by the method of the invention in order to obtain products which remains stable and monolithic for many hundreds of years, and the invention thereby offers a safe and convenient alternative means of handling other than nuclear fuel reprocessing.

WO 2004/006268 A3

STORAGE OF HAZARDOUS MATERIALS

Field of the Invention

This invention relates to a method for the treatment and storage of hazardous materials by encapsulation. More specifically, it is concerned with the encapsulation
5 in cementitious media of materials encountered in the nuclear industry, and has specific application to uranium and so-called Magnox fuel elements.

Background to the Invention

10 Encapsulation has proved to be an especially favoured method for the disposal of certain hazardous materials; specifically it provides a suitable means for the conversion of these materials into a stable and safe form, which allows for long-term storage and/or ultimate disposal. The technique can find particular application in the nuclear industry, where the highly toxic and radioactive nature of the materials
15 involved, and the extended timescales over which the toxicity is maintained, are the principal considerations when devising safe disposal methods.

In co-pending GB patent application No. 0130593.7, the present applicant has disclosed the use of cementitious grouting materials for the encapsulation of fine
20 particulate sized wastes and provided details of a method for the encapsulation of fine particulate materials which comprises treating these materials with at least one microfine hydraulic inorganic filler.

The use of cement based injection grouting in the construction industry is well
25 known from the prior art. Thus, EP-A-412913 teaches the use of a Portland Cement based grout in the consolidation of concrete structures affected by fine cracks, providing a cost-effective means of infilling both superficial and deeper fissures and cavities in such structures, including such as buildings, bridges and dams. Similarly, ZA-A-9209810 is concerned with a pumpable, spreadable grouting composition
30 incorporating a cementitious and/or pozzolanic or equivalent material, and its

application in sealing fissures and cracks, back-filling, providing mass fills in civil and mining works, or lining tunnels.

Also disclosed in the prior art are hydraulic setting compositions comprising particles of Portland Cement together with fine particles of silica fume containing amorphous silica, which are the subject of EP-A-534385 and are used in the production of concrete, mortar or grout having improved fluidity, whilst GB-A-2187727 describes a rapid gelling, hydraulic cement composition which comprises an acrylic gelling agent, a fine filler and Portland Cement, this composition being thixotropic and finding particular application in the formation of bulk infills for underground mining, and in the filling of voids and cavities in construction or civil engineering. A composition which also is useful in general building and construction work, and as an insulating material comprises a particulate filler, cellulose fibres and a cementitious binder, and is disclosed in GB-A-2117753.

Whilst the majority of these compositions of the prior art have a requirement for the addition of water, EP-A-801124 is concerned with a dry mixture, used for fine soil injection grout preparation, the mixture comprising fillers which do not react with water, cement and deflocculant; on addition of water, an agglomerate-free fine grout is formed, and this is easily injected into fine soil.

Thus, the use of such grouting materials in – primarily – civil engineering is well known, and its use in treating fine particulate sized wastes in the nuclear industry is the subject of the above co-pending application. However, whilst attempts have previously been made to encapsulate broken Magnox fuel elements, the treatment of uranium metal and complete Magnox fuel elements involved in nuclear processing has always been reliant on reprocessing techniques, many of which are well known to those skilled in such technology. Nevertheless, there has long been a need for an alternative approach for dealing with such fuel materials, particularly for those cases where reprocessing is especially difficult or hazardous – or, on occasions, impossible.

The present inventors have now found that cured cementitious materials may advantageously be employed for the long term encapsulation of uranium and Magnox fuel elements, as well as fuel element debris, thereby providing a product which remains stable and monolithic for many hundreds of years. Hence, a treatment method is provided which affords much greater efficiency, convenience and safety in handling, and has a consequent beneficial effect both in terms of environmental considerations and cost, thereby satisfying a long felt need in the nuclear industry wherein the waste management of materials is receiving ever greater attention in the global drive to ensure ever higher safety standards.

10

Statements of Invention

Thus, according to the present invention there is provided a method for the encapsulation of a nuclear material which comprises treating the material with an encapsulant which comprises a cementitious material and curing said cementitious material.

15

Generally, the nuclear material comprises a nuclear fuel material such as uranium metal or Magnox fuel elements or fuel element debris. Alternatively, it may comprise, for example, fast reactor fuel, metal oxide fuel or mixed oxide fuel.

20

The cementitious material may typically comprise, for example, Portland Cement or a similar commercially available product.

One or more additional inorganic fillers may optionally be added to the cementitious material; suitable fillers include blast furnace slag, pulverised fuel ash, hydrated lime, finely divided silica, limestone flour and organic and inorganic fluidising agents.

25

The invention also provides a method for the storage of a nuclear material which comprises encapsulation of the material in a cured cementitious material.

30

Description of the Invention

The method of the present invention is of particular value in the treatment of nuclear fuel materials. Such materials may be treated by this method in order to obtain a product which remains stable and monolithic for many hundreds of years, thereby offering a safe and convenient alternative means of handling other than nuclear fuel reprocessing.

There exists a considerable worldwide stock of such nuclear fuel materials which, whilst safely stored for the medium term, requires a suitable route for long term disposal. This accumulation of this material provides powerful evidence of the absence of any suitable method of treatment. However, the present method now offers a safe and convenient technique for their disposal which should provide considerable environmental benefits.

A particular example of the application of the method involves placing the nuclear material in an appropriate container and adding a suitable cementitious material. Elements of the nuclear material may either be arrayed in the container or mixed haphazardly. The cementitious material is then added and allowed to at least partially cure, and the container may then be capped or, alternatively sent directly for storage or final disposal. The capping process involves placing a cap of cement on top of the mixture of nuclear material and cementitious material in the container after this mixture has been allowed to partially cure; the procedure has proved to be especially valuable in ensuring the safe long term storage of the material, and it provides an additional benefit in the reduction of secondary waste.

The container may comprise any container of an appropriate form and size, for example a drum having a capacity in the region of 500 litres. In such a case, the amount of nuclear material which may safely be stored may be up to as many as 52 elements. Preferably, however, the number of elements would be of the order of 22.

Typically, the cementitious material is provided in the form of an aqueous composition with a water content preferably in the region of 40-50% (w/w). Thus, the material may conveniently be pumped under pressure into the container.

5

10

CLAIMS

1. A method for the encapsulation of a nuclear material which comprises treating the material with an encapsulant which comprises a cementitious material and curing said cementitious material.
2. A method as claimed in claim 1 wherein the nuclear fuel material comprises uranium metal or Magnox fuel elements or fuel element debris.
3. A method as claimed in claim 1 or 2 wherein the cementitious material comprises Portland Cement.
4. A method as claimed in any one of claims 1, 2 or 3 wherein the cementitious material additionally comprises one or more inorganic fillers selected from blast furnace slag, pulverised fuel ash, hydrated lime, finely divided silica, limestone flour and organic and inorganic fluidising agents.
5. A method as claimed in any preceding claim wherein the cementitious material is provided in the form of an aqueous composition.
6. A method as claimed in claim 5 wherein the water content of the composition is in the region of 40-50% (w/w).
7. A method as claimed in any preceding claim wherein the nuclear material is placed in an appropriate container and a cementitious material is added and allowed to at least partially cure.
8. A method as claimed in claim 7 wherein elements of the nuclear material are either arrayed in the container or mixed haphazardly.

9. A method as claimed in claim 7 or 8 wherein the container is subsequently capped.
10. A method as claimed in claim 7, 8 or 9 wherein the container comprises a
5 drum having a capacity in the region of 500 litres.
11. A method as claimed in claim 10 wherein the amount of nuclear material stored is up to 52 elements.
- 10 12. A method as claimed in claim 11 wherein the number of elements is of the order of 22.
13. A method for the storage of a nuclear material which comprises encapsulation of the material in a cured cementitious material.

15

20

Intern	Application No
PCT/GB	03/02870

Application No. _____

PCT/GB 03/02870

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G21F9/16 G21F9/30 G21F9/34

B. FIELDS SEARCHED

IPC 7 G21F

WPI Data, PAJ, EPO-Internal

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 02918 A (TERRA ENVIRONMENTAL) 1 February 1996 (1996-02-01) claims 1,22,23,28,31-34,40,41 ---	1,3-6,13
X	US 4 010 108 A (HANSEN LARRY J ET AL) 1 March 1977 (1977-03-01) the whole document ---	1,3-6,13
X	US 4 839 102 A (BERNARD ANDRE ET AL) 13 June 1989 (1989-06-13) claims 1,8 ---	1,3-6,13
X	US 4 416 810 A (NOAKES JOHN E) 22 November 1983 (1983-11-22) claims 1,5 ---	1,3-7,13
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

***X** document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

8 document member of the same patent family

Date of the actual completion of the international search

14 January 2004

Date of mailing of the international search report

22/01/2004

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Deroubaix, P

INTERNATIONAL SEARCH REPORT

Intern - Application No
PCT/GB 03/02870

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 792 385 A (SNYDER THOMAS S ET AL) 20 December 1988 (1988-12-20) abstract -----	1, 13
X	US 4 931 192 A (MCBRIDE MICHAEL A ET AL) 5 June 1990 (1990-06-05) claim 1 -----	1, 13

INTERNATIONAL SEARCH REPORT

Inten .application No
PCT/GB 03/02870

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9602918	A	01-02-1996	AU 3126095 A WO 9602918 A2	16-02-1996 01-02-1996
US 4010108	A	01-03-1977	US 4167491 A	11-09-1979
US 4839102	A	13-06-1989	FR 2607957 A1 CA 1282503 C DE 3780436 D1 DE 3780436 T2 EP 0274927 A1 ES 2033908 T3 JP 63150696 A	10-06-1988 02-04-1991 20-08-1992 21-01-1993 20-07-1988 01-04-1993 23-06-1988
US 4416810	A	22-11-1983	NONE	
US 4792385	A	20-12-1988	CA 1331161 C DE 3874675 D1 DE 3874675 T2 EP 0315001 A1 ES 2034104 T3 JP 1150899 A KR 9704355 B1	02-08-1994 22-10-1992 15-04-1993 10-05-1989 01-04-1993 13-06-1989 27-03-1997
US 4931192	A	05-06-1990	NONE	